

# DRIVERS

QUANTUM MAX			
CLUB	9°	10.5°	12°
LIE	57°	57°	57°
CC	460 CC	460 CC	460 CC
LENGTH	45.75"	45.75"	45.75"
AVAILABILITY	RH/LH	RH/LH	LH Custom Only

QUANTUM MAX D			
CLUB	9°	10.5°	12°
LIE	59°	59°	59°
CC	460 CC	460 CC	460 CC
LENGTH	45.75"	45.75"	45.75"
WMS LENGTH	44.5"	44.5"	44.5"
AVAILABILITY	RH/LH	RH/LH	RH

QUANTUM MAX FAST		
CLUB	10.5°	12°
LIE	59°	59°
CC	460 CC	460 CC
LENGTH	45.75"	45.75"
WMS LENGTH	44.5"	44.5"
AVAILABILITY	RH/LH	RH/LH

QUANTUM TRIPLE DIAMOND			
CLUB	8°	9°	10.5°
LIE	57°	57°	57°
CC	450 CC	450 CC	450 CC
LENGTH	45.75"	45.75"	45.75"
AVAILABILITY	RH	RH/LH	RH/LH

QUANTUM TRIPLE DIAMOND MAX		
CLUB	9°	10.5°
LIE	57°	57°
CC	460 CC	460 CC
LENGTH	45.75"	45.75"
AVAILABILITY	RH/LH	RH/LH

QUANTUM MINI DRIVER		
CLUB	11.5°	13.5°
LIE	57°	57°
CC	340 CC	340 CC
LENGTH	43.75"	43.75"
WOMEN'S LENGTH	N/A	42.75"
AVAILABILITY	RH/LH	RH/LH

# FAIRWAYS

QUANTUM MAX FAIRWAY						
CLUB	LOFT	LIE	LENGTH	WMS LENGTH	CC	AVAILABILITY
3W (Adj)	15°	57°	43.25"	42"	160 CC	RH/LH
3HL (Adj)	16.5°	57°	43.25"	42"	160 CC	RH
5W (Adj)	18°	57.5°	42.75"	41.5"	140 CC	RH/LH
7W	21°	58°	42.25"	41"	135 CC	RH/LH
HVN	20°	57.5°	43"	41.75"	150 CC	RH
9W	24°	59°	41.75"	40.5"	130 CC	RH
11W	27°	60°	41.25"	40"	125 CC	RH

QUANTUM MAX D FAIRWAY						
CLUB	LOFT	LIE	LENGTH	WMS LENGTH	CC	AVAILABILITY
3W (Adj)	15°	58°	43.25"	42"	190cc	RH/LH
3HL (Adj)	16.5°	58°	43.25"	42"	190cc	RH
5W (Adj)	18°	58.5°	42.75"	41.5"	170cc	RH/LH
7W	21.5°	59°	42.25"	41"	165cc	RH

QUANTUM MAX FAST FAIRWAY						
CLUB	LOFT	LIE	LENGTH	WMS LENGTH	CC	AVAILABILITY
3W (Adj)	16°	58°	43.25"	42"	170 CC	RH
5W (Adj)	19°	58.5°	42.75"	41.5"	150 CC	RH
7W	22°	59°	42.25"	41"	145 CC	RH
9W	25°	59.5°	41.75"	40.5"	140 CC	RH

QUANTUM TRIPLE DIAMOND FAIRWAY					
CLUB	LOFT	LIE	LENGTH	CC	AVAILABILITY
3W (Adj)	15°	55°	43.25"	160 CC	RH/LH
5W (Adj)	18°	55.5°	42.75"	150 CC	LH Custom Only
7W	21°	56°	42.25"	140 CC	RH

QUANTUM TI FAIRWAY					
CLUB	LOFT	LIE	LENGTH	CC	AVAILABILITY
3W	15°	56°	43.25"	170 CC	RH/LH
5W	18°	56.5°	42.75"	155 CC	LH Custom Only

# UTILITY

APEX UW PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	SWINGWEIGHT	AVAILABILITY
17	17°	58.25°	42.25"	D3	RH
19	19°	59°	41.5"	D3	RH/LH
21	21°	59.75°	40.75"	D3	RH/LH
23	23°	60.5°	40"	D3	RH

APEX TI SUPER HYBRID PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	SWINGWEIGHT	AVAILABILITY
2H	16°	57.5°	41.5"	D1	RH
3H	18°	58.125°	40.875"	D1	RH/LH
4H	21°	58.75°	40.25"	D1	RH/LH
5H	24°	59.375°	39.625"	D1	RH

# HYBRIDS

QUANTUM MAX HYBRID					
CLUB	LOFT	LIE	LENGTH	CC	AVAILABILITY
3H (Adj)	19°	58.75°	40.75"	105 CC	RH/LH
4H (Adj)	21°	59.375°	40.125"	106 CC	RH/LH
5H (Adj)	24°	60°	39.5"	100 CC	RH/LH
6H (Adj)	27°	60.625°	38.875"	94 CC	RH
7H (Adj)	30°	61.25°	38.25"	89 CC	RH
8H (Adj)	33°	61.875°	37.625"	86 CC	RH

QUANTUM MAX OS HYBRID						
CLUB	LOFT	LIE	LENGTH	WMS LENGTH	CC	AVAILABILITY
3H (Adj)	18°	58.75°	40.75"	39.75"	130 CC	RH/LH
4H (Adj)	20°	59.375°	40.125"	39.125"	126 CC	RH/LH
5H (Adj)	23°	60°	39.5"	38.5"	121 CC	RH/LH
6H (Adj)	26°	60.625°	38.875"	37.875"	115 CC	RH
7H (Adj)	29°	61.25°	38.25"	37.25"	110 CC	RH
8H (Adj)	32°	61.875°	37.625"	36.625"	107 CC	RH

QUANTUM MAX FAST HYBRID						
CLUB	LOFT	LIE	LENGTH	WMS LENGTH	CC	AVAILABILITY
4H (Adj)	22°	59.375°	40.125"	38.875"	122 CC	RH
5H (Adj)	25°	60°	39.5"	38.25"	115 CC	RH
6H (Adj)	28°	60.625°	38.875"	37.625"	110 CC	RH
7H (Adj)	31°	61.25°	38.25"	37"	105 CC	RH
8H (Adj)	34°	61.875°	37.625"	36.375"	100 CC	RH

# IRONS

APEX TI FUSION 250 PLATED IRON PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
5	23°	61°	38.5"	4.65	RH
6	26°	61.625°	37.875"	4.24	RH
7	30°	62.25°	37.25"	3.66	RH
8	34°	62.875°	36.625"	3.1	RH
9	38°	63.5°	36"	2.54	RH
P	42°	63.75°	35.75"	2.03	RH
A	47°	64°	35.5"	1.9	RH

APEX TI FUSION PLATED IRON PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
4	21°	60.5°	38.5"	3.9	RH/LH
5	23.5°	61°	38"	3.6	RH/LH
6	26.5°	61.5°	37.5"	3.3	RH/LH
7	30.5°	62°	37"	2.9	RH/LH
8	34.5°	62.5°	36.5"	2.5	RH/LH
9	38.5°	63°	36"	2.2	RH/LH
P	43°	63.25°	35.75"	1.8	RH/LH
A	48°	63.5°	35.5"	1.5	RH/LH

# IRONS

APEX Ai150 PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
3	20°	60°	39"	3.35	RH
4	22°	60.5°	38.5"	3.18	RH/LH
5	24°	61°	38"	3	RH/LH
6	27°	61.5°	37.5"	2.72	RH/LH
7	31°	62°	37"	2.36	RH/LH
8	35°	62.5°	36.5"	2.01	RH/LH
9	39°	63°	36"	1.65	RH/LH
P	44°	63.25°	35.75"	1.52	RH/LH
A	48°	63.5°	35.5"	1.4	RH/LH

APEX Ai200 PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
4	21°	60.5°	38.5"	3.8	RH/LH
5	23°	61°	38"	3.7	RH/LH
6	26°	61.5°	37.5"	3.4	RH/LH
7	30°	62°	37"	3.1	RH/LH
8	34°	62.5°	36.5"	2.7	RH/LH
9	38°	63°	36"	2.4	RH/LH
P	43°	63.25°	35.75"	2.0	RH/LH
A	48°	63.5°	35.5"	1.8	RH/LH

APEX Ai300 PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
4	20°	60.375°	39.125"	5.1	RH/LH
5	22°	61°	38.5"	4.8	RH/LH
6	25°	61.625°	37.875"	4.5	RH/LH
7	29°	62.25°	37.25"	4.0	RH/LH
8	33°	62.875°	36.625"	3.6	RH/LH
9	37°	63.5°	36"	3.0	RH/LH
P	42°	63.75°	35.75"	2.4	RH/LH
A	47°	64°	35.5"	1.8	RH/LH

X FORGED IRON PRODUCT SPECIFICATIONS					
CLUB	LOFT	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
4	23°	60.5°	38.5"	3.18	RH
5	26°	61°	38"	2.97	RH
6	29°	61.5°	37.5"	2.74	RH
7	33°	62°	37"	2.44	RH
8	37°	62.5°	36.5"	2.16	RH
9	41°	63°	36"	1.88	RH
P	46°	63.25°	35.75"	1.55	RH

# IRONS

QUANTUM MAX IRON						
CLUB	LOFT	HL SPEC*	LIE	LENGTH	OFFSET (MM)	AVAILABILITY
4	19°	21°	60.375°	39.125"	5.08	RH/LH
5	22°	24°	61°	38.5"	4.67	RH/LH
6	25°	27°	61.625°	37.875"	4.24	RH/LH
7	29°	31°	62.25°	37.25"	3.71	RH/LH
8	33°	35°	62.875°	36.625"	3.15	RH/LH
9	37°	39°	63.5°	36"	2.59	RH/LH
P	42°	44°	63.75°	35.75"	1.91	RH/LH
A	47°	49°	64°	35.5"	1.60	RH/LH
G	51°	53°	64°	35.5"	1.37	RH/LH
S	55°	57°	64°	35.25"	1.12	RH/LH

QUANTUM MAX OS IRON							
CLUB	LOFT	HL SPEC*	LIE	LENGTH	WOMEN'S LENGTH	OFFSET (MM)	AVAILABILITY
4	19°	21°	60.375°	39.125"	38.125"	6.35	RH/LH
5	22°	24°	61°	38.5"	37.5"	5.89	RH/LH
6	25°	27°	61.625°	37.875"	36.875"	5.41	RH/LH
7	29°	31°	62.25°	37.25"	36.25"	4.80	RH/LH
8	33°	35°	62.875°	36.625"	35.625"	4.19	RH/LH
9	37°	39°	63.5°	36"	35"	3.56	RH/LH
P	42°	44°	63.75°	35.75"	34.75"	2.79	RH/LH
A	47°	49°	64°	35.5"	34.5"	2.21	RH/LH
G	51°	53°	64°	35.5"	34.5"	1.65	RH/LH
S	55°	57°	64°	35.25"	34.25"	1.12	RH/LH

QUANTUM MAX FAST IRON						
CLUB	LOFT	LIE	LENGTH	WOMEN'S LENGTH	OFFSET (MM)	AVAILABILITY
5	22°	60.75°	38.75"	37.75"	5.72	RH
6	25°	61.375°	38.125"	37.125"	5.18	RH
7	28°	62°	37.5"	36.5"	4.67	RH
8	32°	62.5°	36.875"	35.875"	4.41	RH
9	37°	63°	36.25"	35.25"	3.61	RH
P	42°	63.25°	36"	35"	3.07	RH
A	46°	63.5°	35.75"	34.75"	2.06	RH
G	50°	63.75°	35.5"	34.5"	2.06	RH
S	56°	64°	35.25"	34.25"	2.06	RH

# WEDGES

CB12 WEDGE PRODUCT SPECIFICATIONS									
	LOFT/BOUNCE	SOLE GRIND	LENGTH	LIE	SWING WEIGHT (STEEL)	SWING WEIGHT (GRAPHITE)	MEN'S HAND	WOMEN'S HAND	WOMEN'S SWING WEIGHT
GAP	50°/12°	TRI-LEVEL	35.5"	64°	D2	C8	RH/LH	LH Custom Only	LH Custom Only
	52°/12°	TRI-LEVEL	35.5"	64°	D2	C8	RH/LH	RH	C2
SAND	54°/14°	TRI-LEVEL	35.25"	64°	D3	C9	RH/LH	RH	C4
	56°/14°	TRI-LEVEL	35.25"	64°	D3	C9	RH/LH	RH	C4
LOB	58°/12°	TRI-LEVEL	35"	64°	D3	C9	RH/LH	RH	C4
	60°/12°	TRI-LEVEL	35"	64°	D3	C9	RH/LH	RH	C4

OPUS SP PRODUCT SPECIFICATIONS											
	LOFT/BOUNCE	SOLE GRIND	STANDARD LENGTH	LIE ANGLE	SWING WEIGHT (STEEL)	SWING WEIGHT (GRAPHITE)	BLACK SHADOW	BRUSHED CHROME	WM'S SWING WEIGHT	WM'S AVAILABILITY	WM'S LENGTH
PW	48°   10°	S	35.75"	64°	D3	C9	RH	RH			
	50°   10°	S	35.5"	64°	D3	C9	RH/LH	RH/LH			
	50°   12°	W	35.5"	64°	D3	C9	RH	RH			
SAND	52°   10°	S	35.5"	64°	D3	C9	RH/LH	RH/LH	C4	RH	35.625"
	52°   12°	W	35.5"	64°	D3	C9	RH	RH	C4	RH	35.625"
	54°   10°	S	35.25"	64°	D5	D1	RH/LH	RH/LH			
	54°   14°	W	35.25"	64°	D5	D1	RH	RH			
	54°   12°	X	35.25"	64°	D5	D1	RH	RH			
	56°   8°	C	35.25"	64°	D5	D1	RH	RH			
	56°   10°	S	35.25"	64°	D5	D1	RH/LH	RH/LH	C6	RH	35.375"
	56°   14°	W	35.25"	64°	D5	D1	RH/LH	RH/LH	C6	RH	35.375"
	56°   12°	X	35.25"	64°	D5	D1	RH/LH	RH/LH			
	LOB	58°   6°	T	35"	64°	D5	D1	RH	RH		
58°   8°		C	35"	64°	D5	D1	RH	RH/LH			
58°   10°		S	35"	64°	D5	D1	RH/LH	RH/LH			
58°   12°		X	35"	64°	D5	D1	RH	RH			
58°   14°		W	35"	64°	D5	D1	RH	RH/LH			
60°   6°		T	35"	64°	D5	D1	RH/LH	RH/LH			
60°   8°		C	35"	64°	D5	D1	RH	RH/LH			
60°   10°		S	35"	64°	D5	D1	RH/LH	RH/LH	C6	RH	35.125"
60°   12°		X	35"	64°	D5	D1	RH/LH	RH/LH			
60°   14°		W	35"	64°	D5	D1	RH/LH	RH/LH	C6	RH	35.125"
	62°   5°	T	35"	64°	D5	D1					
	64°   5°	T	35"	64°	D5	D1					

